





We are one of prominent manufacturers, suppliers and exporters of steel Pipe fittings, BW and Forged Pipe Fittings, steel Flanges, Fasteners, Steel Pipes/Tubes, Steel Plates/Sheets, Steel Bars/Rods, etc. In various material grades. Zhengzhou Huitong Pipeline Equipment Co., Ltd. Fax: +86-371-60953359. Mob: +8619339900201.





Hamer(R) Line Blind Valves ensures positive and visible knowledge that a pipeline is blinded with a rotating spectacle plate that shows flow or no-flow incorporates a tough, simple design that provides long-lasting service life with minimal maintenance requirements. The spectacle plate system on all Hamer(R) Line Blind Valves provides a positive, visual indication of the valve's ???



disturbance caused by the exercise of these rights. The Energy Act will also modify certain provisions of the Pipe-lines Act 1962 so as to apply them to the GPSS post sale. Relationship to other legislative proposals: None Background: The Government oil pipeline network ??? the Government Pipe-line and Storage



This is where blind flanges come in. A blind flange is a type of pipe flange that closes off the end of a pipeline. A safety device isolates the pipeline section and assures safety during maintenance or repair work. This ???



Hamer(R) Line Blind Valves ensures positive and visible knowledge that a pipeline is blinded with a rotating spectacle plate that shows flow or no-flow. It incorporates a tough, simple design that provides long-lasting service life with ???





A spectacle blind is a forged product and a combination of a flange spade and a ring spacer in one single product. One end of the spectacle blind will have an opening that allows fluid flow through the pipe during operation and the other end is made solid to block flow during isolation or maintenance time.





This is where blind flanges come in. A blind flange is a type of pipe flange that closes off the end of a pipeline. A safety device isolates the pipeline section and assures safety during maintenance or repair work. This blog post will examine blind flanges and their importance in pipeline isolation. What are Blind Ranges?






In some cases, removing a blind from a pipeline can create a vacuum, which may lead to operational issues or damage to the pipeline. Using a vented paddle blind helps prevent the formation of a vacuum by allowing air to enter the pipeline gradually as the blind is removed. Note: USA Industries positions all NPTs 180? from the handle. The





pipeline is a well established maintenance and safety procedure in the oil, gas, onshore and refining industries. The plate completely covers the bore, and is capable of withstanding the ???



Blind flanges are commonly employed in applications where temporary or permanent closure of pipelines is required, such as during maintenance, repairs, or system isolation. Types of Blind Flanges: Raised Face Blind Flanges: Raised face blind flanges feature a raised ring or face ???





2.1 Physical model. After considering natural convection, a model of the PCM composite pipeline was created as shown in Fig. 1 the model was divided into 5 layers from the inside out, R1 and R2 were the internal and external radius of the steel pipe respectively, R3-R2 was the thickness of the composite phase change material layer, R4 was the outer radius of ???



pipeline was to adopt effective insulation measures. There-fore, the research and development of insulation materials and the design of reasonable pipeline structure have become the research hotspot of improving insulation technology. According to the concept of phase change energy storage, a PCM combined energy storage pipe was proposed in this



A blind flange is a type of pipe fitting used to close the end of a piping system or pressure vessel openings, preventing the flow of fluids or gases. Unlike other types of flanges, a blind flange has no central opening, making it a solid disk that provides a secure seal.



They function similarly to spectacle blinds in that they completely shut off the pipeline. The difference is paddle blinds have extended ends, making them easier to handle while handling heavy-duty applications. Paddle blinds are typically used in high-pressure systems; sometimes, they can be operated without requiring a temporary valve



Spectacle blinds, spades and spaces are a common feature of pipelines or piping in most industries as they are used to enable maintenance work. They can be used to isolate a section of pipe or isolate a specific device so that it can be cleaned, checked and generally looked after. They are fitted in a pipeline between two flanges and







Spectacle blinds are generally purchased from manufacturers of flanges but can be produced by steelworking centers as well. Spectacle blinds (also defined as "spectacle flanges") are produced starting from steel plates and are basically made of two interconnected discs: one is actually a ring (i.e. a disc with a hole of the same bore size as the pipeline), and the other is a solid disc.





This demo can also show how the pipe diameter affects the pressure loss. If I switch in this pipe with the same length as the original sample but which has a smaller diameter, we can see the additional pressure drop that occurs. The smaller pipe has ??? the diameter of the original sample, and diameter has an exponent of 4.9 in our equation





Blinds are flanges without a center bore (hole or opening) and are available in both Raised Face (RF) and Flat Face (FF) styles. While most flange types create a connection point that allows the flow of liquid, gas, or air, blind flanges are used to seal the end of a piping system and prevent flow. Blind flanges may be used when testing pipe pressure, to create an access point in a ???





Spectacle Blinds/Figure 8 Blinds: These versatile devices provide a swift and easy solution for pipeline isolation or reconnection. With their unique design, they allow operators to quickly switch between an open or closed position, streamlining the ???





Blind tees, as important junctions, are widely used in offshore oil and gas transportation systems to improve mixing flow conditions and measurement accuracies in curved pipes. Despite the significance of blind tees, their unsteady flow characteristics and mixing mechanisms in turbulent flow regimes are not clearly established. Therefore, in this study, ???







Task Description ??? This research program focused on the seismic response of pipeline and gas storage surface infrastructure. This surface infrastructure includes river crossings, service risers and gas meter units connected to consumers buildings as well as various facilities, such as storage field facilities, metering and pressure regulating stations, and compressor stations.





A blind flange is a solid steel piece with no bore (interior diameter) and primarily designed to cap off a line. As the majority of flange connections allow for the passing through of air or fluid via an interior opening, blinds give the ends of pipe connections a well formed termination point or rerouting of the media in question towards another portion of the pipe assembly.





It can be used to seal or blind a pipeline or pressure vessel and also can block the flow of the fluid. The blind flanges must be capable enough to withstand the mechanical stress because of the system pressure. This feature is very useful because the pipe doesn't have to be moved when the cam set spectacle plate is changed. So because of





Nowadays, in addition to the well-known solar and wind systems, micro-hydropower systems in pipelines are becoming particularly interesting for the integration of renewable resources for urban and





The composite energy storage pipeline with PCM not only has thermal insulation performance, but also can greatly prolong the safe shutdown time when the shutdown condition occurs by taking advantage of the storage and discharge energy characteristics of PCM. Taking the conventional pipe diameter of ??282 x 4 mm used in the field as an







and the maintenance of all storage capacities* safe and efficient (*compressor, isolation, and vent). STORAGE STATION Installed along the pipe to boost the gas, compression stations are equipped with ONIS Line Blinds to increase safety and cost efficiency of compressor maintenance. Pressure balancing bypasses are used around main pipeline





HDPE Pipe Dimensions and Weights - PE100 PN10 SDR 17. HDPE Pipe Dimensions and Weights - PE100 PN8 SDR 21. HDPE Pipe Dimensions and Weights - PE100 PN6.4 SDR 26. HDPE Pipe Dimensions and Weights - PE100 PN5 SDR 33. Dimensions of PVC Pipes Sch40 as per ASTM D1785. Dimensions of PVC Pipes Sch80 as per ASTM D1785. ???





SLIDING TYPE Sliding type line blind has a unique gear set mechanism that makes a gap to slide in/out a blind plate without pipe joint stretching. It provides a safe and time efficient blinding process. SAMMI Line Blind valves have a sturdy and simple design creates highly reliable and durable line blinds using the most advanced technology.



The blind may be inserted by replacing a spacer ring with a line blind or rotating the blind end of a spectacle blind into place that has been installed on the flange. A spectacle blind is a permanent installation designed to simplify the change-over between a blind and an open-spacer.